



	Standard	Result
 <b>Size</b>		180 x 1220 mm
 <b>Thickness</b>		5.0 mm
<b>Construction</b>		4mm SPC Core / 1mm IXPE Underlay
<b>Locking System</b>		Unipush Fold Down
<b>Built-in Acoustic Underlay</b>		Ideal for Underfloor Heating Systems & Sound Reduction
 <b>Bevel Edge</b>		Micro Bevel
<b>Wear Layer</b>		0.55 mm
<b>Surface Treatment</b>		UV Coating
<b>Guarantee*</b>	Commercial	10 years
	Domestic	Lifetime
 <b>Classification</b>	EN ISO 10582 Light Industrial	General
	EN ISO 10582 Commercial	Heavy
	EN ISO 10582 Domestic	Heavy
 <b>Reaction to Fire</b>	EN 13501-1	Bfl-s1
<b>Resistance to Chemicals</b>	ASTM F925-13	Pass
 <b>Staining Resistance</b>		Pass
 <b>Slip Resistance**</b>	EN13893	DS
 <b>Light Stability</b>	ASTM F1515-15 & ASTM D2244-16	Pass
 <b>Abrasion Resistance</b>	ASTM D4060-14	Index 21.6
<b>Curling</b>	EN434	Pass
 <b>Dimensional Stability</b>	ASTM F 2199-09	Pass (Length -0.01% / Width -0.02%)
<b>Critical Radiant Flux</b>	ASTM E648	1.08 watts/cm2 = Class I Interior Floor Finish
<b>Static Coefficient of Friction</b>	ASTM C1028-07	Pass
 <b>Electrical Behaviour Body Voltage</b>	EN 14041 / EN 1815	Pass - Voltage: 0.5kV
 <b>Residual Indentation</b>	ASTM F1914-07	Pass ≤ 8%
 <b>Resistance to Heat</b>	ASTM F1514-03	Pass / Underfloor Heating Compatible Max 27°C
 <b>VOC Emission</b>	EN 2015 / DIN EN 16516	Class A+
	AgBB-scheme 2015	Pass

\*Subject to terms. Please see our website,

\*\*Slip Resistance can be affected by surface contamination, product maintenance & use,

For more information call DMS Flooring on 01604 664850 or email [sales@dmsflooringsupplies.co.uk](mailto:sales@dmsflooringsupplies.co.uk)



EN14041

Internal use

Notified Body 0766  
Slip Resistance - Class DS  
Reaction to Fire - Class B<sub>fl</sub>-s1